

# Product information

## Truck Series DPF Protector

PI 3/20/08/2019



### Description

Reduces formation of soot during combustion in the engine. Improves engine performance and emissions control. Reduces clogging of the DPF caused by soot as a combustion product.

#### Effect:

- improves the combustion
- cleans the injection system and protects from contaminations
- reduces soot load in the DPF
- improves fuel economy

### Properties

- reduces soot emissions
- regeneration aid for diesel particulate filters
- especially suitable for short trips and city vehicles

### Technical data

Base	Additiv-Kombination in Trägerflüssigkeit / additive mixture in liquid carrier
Color / appearance	hellbraun, klar / light brown, clear
Density at 59 °F	0,842 g/cm <sup>3</sup>
Regulation on Flammable Liquids Class (Germany)	A III
Flash point	145 °F
Pour point	- 97 °F
Form	flüssig / liquid
Odor	charakteristisch / characteristic

### Areas of application

Added to diesel fuel for all diesel engines with DPF, specially designed for trucks and commercial motor vehicles, tractors, construction machinery and stationary engines. Ideally suitable for short distance or short time operated running engine.

### Application

For best results and long-term effect add DPF protector every 2.000 km (1.200 miles). One 500 ml can is sufficient for 115 liters (30 gal.) of Diesel. Minimum fuel filling of 50 liters (14 gal.) is requested for optimum product performance.

### Comment

 **WARNING:** Cancer - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).



### Available pack sizes

500 ml Can sheet metal 20258  
USA (-EN-)

**Our information is based on thorough research and may be considered reliable, although not legally binding.**