

Product information

Truck Series Oil Treatment

PI 15/28/03/2019



Description

Engine Armor with MoS₂. The molybdenum disulfide (MoS₂) in the additive forms a highly-durable lubrication film on all surfaces. High operational security thanks to optimum wear protection.

- Reduces friction and engine wear.
- Ensures the engine runs quietly.
- Reduces the consumption of oil and fuel.

Properties

- excellent wear resistance
- increases operational reliability
- reduces oil and fuel consumption
- minimizes friction
- outstanding emergency-running properties
- increases smooth operation

Technical data

Base	MoS ₂ -Suspension
Color / appearance	schwarz / black
Solids content	~ 3 %
Density at 68 °F	0,9 g/cm ³ DIN 51757
Flash point	394 °F DIN ISO 2592
Pour point	-4 °F DIN ISO 3016
Odor	charakteristisch / characteristic
Form	flüssig / liquid
Viscosity at 104 °F	95 mm ² /s

Areas of application

Suitable for all standard motor oils in gasoline and diesel engines.

Application

The product can be applied anytime, for the maximum performance add directly after the motor oil change. One can is sufficient for up to 7 liters (1.8 gal.) of motor oil. Minimum oil filling of 3 liters (0.8 gal./3.17 U.S. QT) is requested for optimum product performance.

Optimum dosage with approx. 5% of the oil fill capacity.

Comment

Not suitable for use with wet clutches!



Available pack sizes

500 ml Can sheet metal	20256
	USA AND CANADA (-EN-F-)

Our information is based on thorough research and may be considered reliable, although not legally binding.