



Installation Procedures

ECS A3 Fender Marker Installation Instructions

This tutorial is provided as a courtesy by ECS Tuning.

Proper service and repair procedures are vital to the safe, reliable operation of all motor vehicles as well as the personal safety of those performing the repairs. Standard safety procedures and precautions (including use of safety goggles and proper tools and equipment) should be followed at all times to eliminate the possibility of personal injury or improper service which could damage the vehicle or compromise its safety.

Although this material has been prepared with the intent to provide reliable information, no warranty (express or implied) is made as to its accuracy or completeness. Neither is any liability assumed for loss or damage resulting from reliance on this material. SPECIFICALLY, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER WARRANTY IS MADE OR TO BE IMPLIED WITH RESPECT TO THIS MATERIAL. In no event will ECS Tuning, Incorporated or its affiliates be liable for any damages, direct or indirect, consequential or compensatory, arising out of the use of this material.



ECS A3 Fender Marker Installation Instructions

Tools Required:

None



To remove the OEM fender markers, slide the light forward. While holding it forward, pull on the corner of the marker marked E1, the whole assembly will release its self from the fender.

Installation is very simple, insert one side of the marker light, and press the other side in. It will seat with a satisfying click.

**ECS A3 Fender Marker
Installation Instructions**



ECS Tuning
1000 Seville Road, Wadsworth, OH 44281
Phone: 1.800.924.5172 www.ecstuning.com