

Audi  
2009-2012  
pre-facelift  
B8 A4/S4



# RS4-Style Grille Installation

[ES2652272](#)  
[ES2652274](#)  
[ES2818169](#)

This tutorial is provided as a courtesy by ECS Tuning.

Proper service and repair procedures are vital to the safe, reliable operation of all motor vehicles as well as the personal safety of those performing the repairs. Standard safety procedures and precautions (including use of safety goggles and proper tools and equipment) should be followed at all times to eliminate the possibility of personal injury or improper service which could damage the vehicle or compromise its safety.

Although this material has been prepared with the intent to provide reliable information, no warranty (express or implied) is made as to its accuracy or completeness. Neither is any liability assumed for loss or damage resulting from reliance on this material. SPECIFICALLY, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER WARRANTY IS MADE OR TO BE IMPLIED WITH RESPECT TO THIS MATERIAL. In no event will ECS Tuning, Incorporated or its affiliates be liable for any damages, direct or indirect, consequential or compensatory, arising out of the use of this material.

best viewed in Acrobat® Reader®

Installing an ECS Tuning RS4-style mesh Grille on an Audi B8 A4/S4 pre-facelift car is a great weekend project. To do the job properly, you'll need to remove the front bumper cover, but the job is fairly simple, and doesn't require a lot of special or exotic tooling. You'll need a couple of Torx drivers and 10mm sockets with extensions, but no drilling or body mods will be needed.

Available in plain black, black with silver accent, or black with chrome accent, these ECS Tuning grilles are ready to install. You'll have to transfer your Audi emblem over, and they also come with a Euro-plate holder which you can decide if you want to run it or not.



ES2652272

Gloss Black with Gloss Black Frame



ES2652274

Gloss Black with Silver Frame



[ES2818169](#)

Gloss Black with Chrome Frame

## Step 1

Open the hood.

Remove the screws securing the radiator core support cover. Slide the cover rearward and up to remove it.




## Step 2

Remove the two top bumper cover screws, one on either side, located next to the headlights.




### Step 3

Raise the car and remove the main belly pan screws (arrows). OE screws can be removed with common or Phillips head screwdrivers or a T25 Torx® driver



### Step 4

Turn the wheels all the way to one side; remove the two screws and plastic clip holding the fender liner to the bumper cover and chassis.



## Step 5

Reach up inside the fender liners and disconnect both fog lights.



## Step 6


Reach up inside the fender liner and unbolt the fasteners securing the bumper cover to the fender.

We overlaid an illustration to show you the fastener locations. There are two threaded studs pointing downward from the lower edge of the fender and a 6mm bolt (10mm socket) that threads horizontally through the fender into a metal bracket in the bumper cover.

Service Tip: Loosen the two nuts until they are flush with the ends of the studs, but don't remove them.

Unbolt and remove the single bolt.

Do this on both sides



### Step 7

Pull the bumper away from the fender, until the snap clip retainer pops free from its mating tab on the plastic retainer bracket.

Repeat this process at the opposite side.



### Step 8

Grab the bumper in the center at top and bottom and slide it forward slightly. Before removing the bumper cover completely, reach down at the rear top center of the grille and unplug the garage door opener module (if your car has one).


Service Tip: The garage door module is attached to the back of the grille, behind the Audi ring logo, and its plug is more accessible with the bumper cover pulled forward slightly.

(The bumper is not heavy, but may be awkward. You may want to ask an assistant to lend you a hand as you guide the bumper off safely.)



### Step 9

With the bumper cover removed, the aluminum crash bracket is exposed.



### Step 10

For improved appearance, we elect to clean and paint the aluminum bumper bracket. First we apply a coat of plasticized stone shield spray, then final coat with a matte black trim paint.


We will also remove the plastic air deflector (arrow) so it doesn't interfere with the new grille. It just snaps off.



## Step 11

Remove the old grille from the bumper cover.

First, unsnap the foam pad from the rear of the grille and lift it out.




## Step 12

If your car has one, unscrew the mounting bracket for the garage door opener module, and remove the module from the bracket.


The bracket is not a direct-mount fit on your new grille, so we will mount it at an alternate location.



Service Tip: Use any mounting method you choose as long as the module is attached securely: tie wraps, tape, double-backed tape, or possibly a homemade bracket. Just be sure to mount the module safely and close enough to the wiring harness that you can plug it in.



Lift the old grille from the front bumper cover.




### Step 15

Drop the new grille into the bumper. Align the tabs and screw holes as you carefully snap the new grille in place and reinstall the perimeter screws.




### Step 16

If you are reusing them, carefully remove the Audi rings from your old grille. Whether you are reusing your original or if you have purchased new rings, you will have to remove the two alignment pins by simply snipping or cutting them off.



### Step 17

Install the rings onto the new grille by aligning the ten ring hooks (highlighted) with the slots in the grille, then press them firmly into place, making sure all hooks are engaged with the tabs on the grille slots.




### Step 18

With the grille assembled, reverse your steps. Slide the bumper cover onto the front of the car.



## Step 19

The top fender mount has a metal retainer clip that will grip on raised teeth in the grille mounting tab as you slide the bumper in place. These will hold the bumper until you can start the two top screws and thread them in finger-tight.



## Step 20

Pull the rear edge of the bumper toward the wheel opening while inserting the top edge of the bumper cover into the gap between the plastic retainer and fender (arrow).

When the bumper tab is properly aligned with the retainer clip, push the top edge of the bumper cover inward until it snaps in place (arrow).

Replace the fender screw removed in Step 6 and tighten the two nuts on the fender studs, keeping the bumper and fender edges flush as you tighten. Repeat this sequence on the other side.


- Reconnect the fog lamps.
- Replace the fender liner fasteners.
- Reinstall the belly pan.



## Step 21

Lower the car and align the top of the bumper with the headlights. Close the hood to check the grille face-to-hood alignment.

Service Tip: Slide the top grille tabs in or out as needed to align the grille before tightening the two top screws.



## Step 22

Replace the top radiator cover, Slide the tabs at the front of the top cover into the rear top of the grille and install the four screws removed back in Step 1.



Thanks!

For purchasing your blackout grille from  
ECS Tuning.

We appreciate your business and hope  
this tutorial has been helpful.

